



# POWER CORD & LIGHT REELS Series 4000 and 5000

## Better by Design™

### Adjustable Bumper Stop

Allows any desired length of cord to be maintained outside the reel.

### Corrosion-Resistant

Steel components are individually powder coated to virtually eliminate corrosion.

### Reelcraft offers eight styles of outlets and lamps

- Single receptacle
- Duplex outlet box w/ GFCI (F) - 2 styles available
- R.V. plug
- Fluorescent - 2 styles available
- Incandescent - 2 styles available

### Easy to Mount

Attaches to most structurally sound surfaces. Edges are curved for safety.

**NOTE:** Swing brackets should be used if cords are pulled at more than 45°, see page 49.



### Adjustable Guide Arm

Multiple guide arm positions for versatile uses and easier field adjustment.

### Enclosed Drive Spring

Drive mechanism is enclosed for protection against the environment.

### Long Life Drive Spring

Declutching arbor virtually eliminates possibility of spring damage due to reverse winding of reel spool.

### Structural Strength

Robotically welded heavy gauge steel frame.



### MODEL NUMBER SIGNIFICANCE

This chart is for reference purposes only. Reels cannot be ordered by selecting from this chart. Please see Selection Charts on pages 40-41 or consult manufacturer for any questions about option combinations.

#### BUMPER ASSEMBLIES FOR CORD REELS

PART NUMBER	OUTSIDE DIA. OF CORD	CORD SPECIFICATIONS			
		AWG / mm <sup>2</sup>	# Cond.	Type	
600193	.320" - .530"	16 1.33	3	SJO	
1-HR1004-A	.438" - .624"	12 3.32	3	SJO	
600267	.645"	10 5.37	3	SO	
1-HR1004	.625" - .749"	12 3.32	3	SO	
3-HR1004-3	1.06" - 1.30"	6 8.00	3	SO	

### SERIES 4000 and 5000 CORD REELS

FOR REFERENCE ONLY

**L 40501633**

#### LATCH TYPE

L = LATCHING  
C = CONSTANT TENSION

#### REEL SERIES

40 = 4000 SERIES REEL  
45 = 4500 SERIES REEL  
55 = 5500 SERIES REEL  
57 = 5700 SERIES REEL

#### WIRE SIZE

10 = 10 GAUGE  
12 = 12 GAUGE  
16 = 16 GAUGE

#### LENGTH OF CORD

00 = W/O CORD  
35 = 35 FEET  
45 = 45 FEET  
50 = 50 FEET

#### NO. OF CONDUCTORS

2 = TWO CONDUCTOR  
3 = THREE CONDUCTOR

#### STYLE NUMBERS

NONE. OPEN END  
1 = INCANDESCENT LAMP  
2 = FLUORESCENT LAMP  
3 = SINGLE RECEPTACLE  
4 = R.V. PLUG (M)  
5 = INCANDESCENT NON-SPARKING  
6x = FLUORESCENT EXPLOSION PROOF  
7 = DUPLEX OUTLET BOX (F) W/GFCI  
8 = FLUORESCENT W/OUTLET

CSA CERTIFIED

UL LISTED

North America: 800-444-3134 Asia: +63 (45) 625-6624  
Europe: +44 (0) 1536 406999 Latin America: 260-489-1685

www.reelcraft.com



**REELCRAFT**

Wind Things Up With Reelcraft™