




COMPLETE WELDING SERIES

Series TW and BA

FEATURES

- ✓ Designed to increase safety in the work area with a resulting increase in productivity and efficiency
- ✓ Full flow shaft swivels
- ✓ Independent dual swivel body manufactured from aluminum and hard coated for wear resistance assures positive separation of gases due to its unique design
- ✓ Double-sealed, "O" rings prevent leakage
- ✓ Swivel body and inlet are both permanently identified with machined grooves on the acetylene side to assure proper installation
- ✓ Durable abrasion and corrosion resistant baked-on red powder-coated finish
- ✓ Reel frame, spool and drum are fabricated of heavy gauge steel
- ✓ Temperature operating range - 20° F / -29° C to +250° F / +120° C



Dual swivel is an exclusive Reelcraft design

Independent dual swivel body manufactured from aluminum and hard coated for wear resistance. Assures positive separation of gases due to its unique design.

Double - sealed, special molded "O" rings prevent leakage. Swivel body and inlet are both permanently identified with machined grooves on the acetylene side to assure proper installation. Available with TW 5000 and TW 7000 series reels.

NEW!



Economical

Lightweight for hose lengths up to 50'

STW3450 OLP
*See page 19 for additional details.
Made in Australia



UL LISTED
TW7450 OLP

Most Popular

Spring driven for hose lengths up to 60'

High Volume

Dual welding, spring driven for high volume of gas



UL LISTED

Available in T grade only TW84100 OLPT

"T" GRADE FUEL GAS REELS

"T" grade hose reels are used for a wide variety of gases such as mapp gas, propane gas, natural gas and fuel gases.

When ordering any welding hose reels you must specify the type of gas being used.

To order "T" Grade reels, add a suffix "T" to the TW Models. Example - TW 5425 OLPT.

North America: **800-444-3134** Asia: **+63 (45) 625-6624**
Europe: **+44 (0) 1536 406999** Latin America: **260-489-1685**

www.reelcraft.com



Wind Things Up With Reelcraft™