



MULTI CONFIGURATIONS

Safe-T-Reel Series

Safe-T-Reel™ Series

Up to 150' fuel gas

Up to 200' 12/3 cable

Ideal for applications where space, weight and flexibility are key, these reels are designed for manual winding of air/water/fuel gases hose, electric cord and welding cable. Versatile in function, select configurations to suit specific needs. Safe-T-Reels™ offer trouble-free management of large capacities of hose or cord.



T-2462-0

Dual Spool

Side-by-side combinations

Dual Spool

Stacked combinations



T-2464-0

Single Spool

SINGLE SPOOL REELS

MODEL	AMP	REEL CAPACITY		WEIGHT	CABLE	A	B	E
		ft / in	lbs / kg					
SINGLE WELDING CABLE 600 V								
T-1460-0 CA	300	200	60	22 10	-----	19 483	18 457	16 1/4 413
SINGLE POWER CABLE - 3 CONDUCTOR								
T-1535-003	35	200	60	22 10	8 / 3	19 483	18 457	15 3/4 400
T-1535-083-100*	33	100	30	50 23	8 / 3	19 483	18 457	15 3/4 400
T-1535-103-200*	24	200	60	81 37	10 / 3	19 483	18 457	15 3/4 400
T-1535-123-100*	25	100	30	46 21	12 / 3	19 483	18 457	15 3/4 400
T-1535-123-200*	20	200	60	71 32	12 / 3	19 483	18 457	15 3/4 400

* includes cable

DUAL SPOOL REELS

MODEL	AMP	REEL CAPACITY		WEIGHT	A	B	E
		ft / m	lbs / kg				
DUAL SIDE-BY-SIDE WELDING CABLE (2) 600 V							
T-2462-0	300	200	60	50 23	19 483	18 457	29 737
DUAL STACKED WELDING CABLE (2) 600 V							
T-2464-0	300	200	60	59 28	38 965	18 457	16 1/4 413
DUAL SIDE-BY-SIDE POWER CABLE / AIR HOSE							
T-2735-2-0*	35	200' / 150'	39.5	18	19 483	18 457	29 737

* Air hose side has 1/2" (12.7mm) inlet

SINGLE SPOOL REELS

MODEL	HOSE I.D.		HOSE O.D.		CAPACITY		WEIGHT		PRESSURE		A	B	E
	in / mm	in / mm	in / mm	in / mm	ft / m	lbs / kg	psi / bar	psi / bar	in / mm	in / mm			
SINGLE AIR/WATER Maximum temperature 150° F (65° C)													
T-1115-08	1/2	13	.844	22	150	45	17.5	8	300	21	19 483	18 457	15 3/4 400
T-1116-08	1/2	13	.844	22	250	76	17.5	8	300	21	19 483	18 457	21 3/4 552
T-1117-12	3/4	19	1.188	31	50	15	22	10	250	18	19 483	18 457	15 3/4 400
T-1118-12	3/4	19	1.188	31	75	23	22	10	250	18	19 483	18 457	21 3/4 552
SINGLE OXYGEN-ACETYLENE T-GRADE SEALS Maximum temperature 150° F (65° C)													
T-1225-04 CA	1/4	6	.530	14	150	45	19	9	200	14	19 483	18 457	16 1/8 410
T-1225-04-100T	1/4	6	.530	14	100	30	44	20	200	14	19 483	18 457	16 1/8 410
T-1226-06	3/8	10	.625	16	100	30	19	9	200	14	19 483	18 457	16 1/8 410

Caution: Compressed air hoses should not be converted to oxygen service. Compressed air hoses are often contaminated with an oil coating, which can react explosively when oxygen is introduced. Oxygen/Acetylene cannot be combined with welding cable or power cord. **Note:** Models listed are without hose and/or cable. Weights listed above are actual product weight without packaging materials. Safe-T-Reels™ are available with cable or hose and in various combinations. Please consult Reelcraft customer service for additional information.



Hose and cable not included.

T-1225-04-100T

Made in USA


Detail of our heavy duty shaft with tapered roller bearing for high rigidity




Shaft sizes are 1 to 1.25" in diameter, supported by tapered roller bearings with 2 to 2.3" housings.

DIMENSIONS


MODEL	C	D
	inches	
T-1115 / T-1117	6	6.5
T-1225 / T-1226	6	6.5
T-1460 / T-1535	6	6.5
T-1116 / T-1118	6	12.5



T-2462	6	6.5
T-2735	6	6.5



T-2464	6	6.5
--------	---	-----



All reels have four 1/2" (13 mm) diameter mounting holes

North America: 800-444-3134 Asia: +63 (45) 625-6624
Europe: +44 (0) 1536 406999 Latin America: 260-489-1685

www.reelcraft.com



REELCRAFT

Wind Things Up With Reelcraft™